




# 750V HPD IGBT Power Module AEP820B08TFLT

**DATASHEET**

V1.1, 2024/11



## Applications

- Motor Drives
- All-Terrain Vehicles
- Automotive Applications
- Hybrid Electrical Vehicles (H) EV
- Commercial Agriculture Vehicles

## Features

### Electrical Features

---

- Low  $Q_G$
- $T_{j,op} = 150^{\circ}C$
- Low Inductance Design
- Blocking Voltage 750V
- Fast and Soft Reverse Recovery
- Low  $V_{CE,sat}$  and Switching Losses


### Mechanical Features

---

- Compact Design
- 4.2kV DC Insulation
- UL 94 Module Frame
- Temperature Sensor Included
- Direct Water Cooling Pin-Fin Base Plate
- Easy to Integrate 6-pack Topology
- Pb-free Device and RoHS Compliant
- Guiding Elements for PCB and Cooler Assembly



## Circuit Diagram





## IGBT

### Maximum Rated Values

Parameter	Conditions	Symbol	Values	Unit
Collector-emitter voltage	$T_j = 25^\circ\text{C}$	$V_{CES}$	750	V
Gate-emitter peak voltage		$V_{GES}$	$\pm 20$	V
Implemented collector current		$I_{CN}$	820	A
Continuous DC collector current	$T_F = 70^\circ\text{C}, T_{j,max} = 175^\circ\text{C}$	$I_{C\ nom}$	450	A
Repetitive peak collector current	$t_p = 1\ \text{ms}$	$I_{CRM}$	1640	A
Maximum junction temperature		$T_{j,max}$	175	$^\circ\text{C}$

### Characteristics Values

Parameter	Conditions		Symbol	Min.	Typ.	Max.	Unit
Collector-emitter saturation voltage	$I_C = 450\text{A}, V_{GE} = 15\text{V}$	$T_j = 25^\circ\text{C}$	$V_{CE,sat}$		1.15	1.45	V
	$I_C = 450\text{A}, V_{GE} = 15\text{V}$	$T_j = 150^\circ\text{C}$			1.25		
	$I_C = 450\text{A}, V_{GE} = 15\text{V}$	$T_j = 175^\circ\text{C}$			1.30		
	$I_C = 820\text{A}, V_{GE} = 15\text{V}$	$T_j = 25^\circ\text{C}$			1.40		
	$I_C = 820\text{A}, V_{GE} = 15\text{V}$	$T_j = 150^\circ\text{C}$			1.60		
	$I_C = 820\text{A}, V_{GE} = 15\text{V}$	$T_j = 175^\circ\text{C}$			1.70		
Gate threshold voltage	$I_C = 9.6\ \text{mA}, V_{CE} = V_{GE}$	$T_j = 25^\circ\text{C}$	$V_{GE,th}$	5.10	5.70	6.50	V
	$I_C = 9.6\ \text{mA}, V_{CE} = V_{GE}$	$T_j = 150^\circ\text{C}$			4.20		
	$I_C = 9.6\ \text{mA}, V_{CE} = V_{GE}$	$T_j = 175^\circ\text{C}$			3.95		
Collector-emitter cut-off current	$V_{CE} = 750\text{V}, V_{GE} = 0\text{V}$	$T_j = 25^\circ\text{C}$	$I_{CES}$			1.0	mA
	$V_{CE} = 750\text{V}, V_{GE} = 0\text{V}$	$T_j = 150^\circ\text{C}$				5.0	
	$V_{CE} = 750\text{V}, V_{GE} = 0\text{V}$	$T_j = 175^\circ\text{C}$				10.0	
Gate-emitter leakage current	$V_{CE} = 0\text{V}, V_{GE} = 20\text{V}$	$T_j = 25^\circ\text{C}$	$I_{GES}$			400	nA
Gate charge	$V_{GE} = -8\text{V} / +15\ \text{V}$	$T_j = 25^\circ\text{C}$	$Q_G$		1.8		$\mu\text{C}$
	$I_C = 450\text{A}, V_{CE} = 400\text{V}$						
Internal gate resistance		$T_j = 25^\circ\text{C}$	$R_{G,int}$		1.7		$\Omega$
Input capacitance	$f = 100\text{kHz}, V_{CE} = 50\text{V}$	$T_j = 25^\circ\text{C}$	$C_{ies}$		43		nF
	$V_{GE} = 0\text{V}$						
Output capacitance	$f = 100\text{kHz}, V_{CE} = 50\text{V}$	$T_j = 25^\circ\text{C}$	$C_{oes}$		2.1		nF
	$V_{GE} = 0\text{V}$						
Reverse transfer capacitance	$f = 100\text{kHz}, V_{CE} = 50\text{V}$	$T_j = 25^\circ\text{C}$	$C_{res}$		0.6		nF
	$V_{GE} = 0\text{V}$						



# AEP820B08TFLT HPD IGBT Power Module

ACTRON TECHNOLOGY CORP.

Parameter	Conditions	Symbol	Min.	Typ.	Max.	Unit
Turn-on delay time, inductive load	$I_C = 450A, V_{CE} = 400V$	$T_j = 25^\circ C$	$t_{d(on)}$	0.14		$\mu s$
	$V_{GE} = -8V / +15V$	$T_j = 150^\circ C$		0.11		
	$R_{G,on} = 2.5 \Omega$	$T_j = 175^\circ C$		0.11		
Rise time, inductive load	$I_C = 450A, V_{CE} = 400V$	$T_j = 25^\circ C$	$t_r$	0.069		$\mu s$
	$V_{GE} = -8V / +15V$	$T_j = 150^\circ C$		0.070		
	$R_{G,on} = 2.5 \Omega$	$T_j = 175^\circ C$		0.072		
Turn-on energy loss per pulse	$I_C = 450A, V_{CE} = 400V$	$T_j = 25^\circ C$ $T_j = 150^\circ C$ $T_j = 175^\circ C$	$E_{on}$	8.7		mJ
	$L_S = 30nH$			12.5		
	$V_{GE} = -8V / +15V$			13.2		
	$R_{G,on} = 2.5 \Omega$					
	$di/dt = 5.5 A/ns (25^\circ C)$ $di/dt = 5.1 A/ns (150^\circ C)$					
Turn-off delay time, inductive load	$I_C = 450A, V_{CE} = 400V$	$T_j = 25^\circ C$	$t_{d(off)}$	0.55		$\mu s$
	$V_{GE} = -8V / +15V$	$T_j = 150^\circ C$		0.56		
	$R_{G,off} = 5.0 \Omega$	$T_j = 175^\circ C$		0.57		
Fall time, inductive load	$I_C = 450A, V_{CE} = 400V$	$T_j = 25^\circ C$	$t_f$	0.27		$\mu s$
	$V_{GE} = -8V / +15V$	$T_j = 150^\circ C$		0.42		
	$R_{G,off} = 5.0 \Omega$	$T_j = 175^\circ C$		0.45		
Turn-off energy loss per pulse	$I_C = 450A, V_{CE} = 400V$	$T_j = 25^\circ C$ $T_j = 150^\circ C$ $T_j = 175^\circ C$	$E_{off}$	30.5		mJ
	$L_S = 30nH$			40.5		
	$V_{GE} = -8V / +15V$			44.7		
	$R_{G,off} = 5.0 \Omega$					
	$dv/dt = 2.5 V/ns (25^\circ C)$ $dv/dt = 2.2 V/ns (150^\circ C)$					
Short circuit current	$V_{GE} = 15V, V_{CC} = 400V$	$T_j = 25^\circ C$	$I_{sc}$	4800		A
	$t_p = 6 \mu s$	$T_j = 175^\circ C$		3800		
	$t_p = 3 \mu s$					
Thermal resistance, junction to cooling fluid	Per IGBT $dV/dT = 10 dm^3/min$ $T_F = 70^\circ C$		$R_{th,jf}$	0.120	0.140	K/W
Operated temperature condition			$T_{j,op}$	-40	150	$^\circ C$



## Diode

### Maximum Rated Values

Parameter	Conditions	Symbol	Values	Unit
Repetitive peak reverse voltage	$T_j = 25^\circ\text{C}$	$V_{RRM}$	750	V
Implemented forward current		$I_{FN}$	820	A
Continuous DC forward current	$T_F = 70^\circ\text{C}, T_{j,max} = 175^\circ\text{C}$	$I_F$	450	A
Repetitive peak forward current	$t_p = 1\text{ ms}$	$I_{FRM}$	1640	A

### Characteristics Values

Parameter	Conditions	Symbol	Typ.	Max.	Unit	
Forward voltage	$I_F = 450\text{A}, V_{GE} = 0\text{V}$	$V_F$	$T_j = 25^\circ\text{C}$	1.45	1.65	V
	$I_F = 450\text{A}, V_{GE} = 0\text{V}$		$T_j = 150^\circ\text{C}$	1.50		
	$I_F = 450\text{A}, V_{GE} = 0\text{V}$		$T_j = 175^\circ\text{C}$	1.55		
	$I_F = 820\text{A}, V_{GE} = 0\text{V}$		$T_j = 25^\circ\text{C}$	1.80		
	$I_F = 820\text{A}, V_{GE} = 0\text{V}$		$T_j = 150^\circ\text{C}$	1.85		
	$I_F = 820\text{A}, V_{GE} = 0\text{V}$		$T_j = 175^\circ\text{C}$	1.90		
Peak reverse recovery current	$I_F = 450\text{A}, V_R = 400\text{V}$ $V_{GE} = -8\text{V}$ $-di_F/dt = 5.0\text{ A/ns (25}^\circ\text{C)}$ $-di_F/dt = 4.1\text{ A/ns (150}^\circ\text{C)}$	$I_{RM}$	$T_j = 25^\circ\text{C}$	225	A	
			$T_j = 150^\circ\text{C}$	275		
			$T_j = 175^\circ\text{C}$	290		
Recovered charge	$I_F = 450\text{A}, V_R = 400\text{V}$ $V_{GE} = -8\text{V}$ $-di_F/dt = 5.0\text{ A/ns (25}^\circ\text{C)}$ $-di_F/dt = 4.1\text{ A/ns (150}^\circ\text{C)}$	$Q_{rr}$	$T_j = 25^\circ\text{C}$	12.5	$\mu\text{C}$	
			$T_j = 150^\circ\text{C}$	31.3		
			$T_j = 175^\circ\text{C}$	35.8		
Reverse recovery energy	$I_F = 450\text{A}, V_R = 400\text{V}$ $V_{GE} = -8\text{V}$ $-di_F/dt = 5.0\text{ A/ns (25}^\circ\text{C)}$ $-di_F/dt = 4.1\text{ A/ns (150}^\circ\text{C)}$	$E_{rec}$	$T_j = 25^\circ\text{C}$	3.5	mJ	
			$T_j = 150^\circ\text{C}$	7.7		
			$T_j = 175^\circ\text{C}$	9.1		
Thermal resistance, junction to cooling fluid	Per diode $dV/dT = 10\text{ dm}^3/\text{min}$ $T_F = 70^\circ\text{C}$	$R_{th,JF}$	0.175	0.200	K/W	



## NTC-Thermistor

Parameter	Conditions	Symbol	Min.	Typ.	Max.	Unit
Rated resistance	$T_c = 25^\circ\text{C}$	$R_{25}$		5.0		k $\Omega$
Resistance tolerance	$T_c = 100^\circ\text{C}, R_{100} = 493 \Omega$	$\Delta R/R$	-5		5	%
B-value	$R_2 = R_{25} \exp [B_{25/50}(1/T_2 - 1/(298 \text{ K}))]$	$B_{25/50}$		3375		K
B-value	$R_2 = R_{25} \exp [B_{25/80}(1/T_2 - 1/(298 \text{ K}))]$	$B_{25/80}$		3411		K
B-value	$R_2 = R_{25} \exp [B_{25/100}(1/T_2 - 1/(298 \text{ K}))]$	$B_{25/100}$		3433		K

## Module

Parameter	Conditions	Symbol	Value	Unit
Isolation test voltage	RMS, f = 0 Hz, t = 1 sec	$V_{\text{ISOL}}$	4.2	kV
Module baseplate material			Cu + Ni	
Module internal isolation material	Basic isolation (class 1, IEC 61140)		$\text{Al}_2\text{O}_3$	
Creepage distance	Terminal to heatsink	$d_{\text{Creep,TH}}$	9.0	mm
Creepage distance	Terminal to terminal	$d_{\text{Creep,TT}}$	9.0	mm
Clearance distance	Terminal to heatsink	$d_{\text{Clear,TH}}$	4.5	mm
Clearance distance	Terminal to terminal	$d_{\text{Clear,TT}}$	4.5	mm
Comparative tracking index <sup>1)</sup>		CTI	> 200	

Parameter	Conditions	Symbol	Min.	Typ.	Max.	Unit
Module stray inductance		$L_{\text{SCE}}$		7		nH
Storage temperature		$T_{\text{stg}}$	-40		125	$^\circ\text{C}$
Mounting torque for module mounting	Screw M4 baseplate to heatsink	M	1.80	2.00		Nm
Weight		G		750		g


<sup>1)</sup> Extracted by following UL 746A



## Characteristics Diagrams


IGBT, Output characteristics

$V_{GE} = 15V, I_C = f(V_{CE})$




IGBT, Output characteristics

$T_j = 25^\circ\text{C}, I_C = f(V_{CE})$




IGBT, Output characteristics

$T_j = 150^\circ\text{C}, I_C = f(V_{CE})$



Diode, Forward characteristics

$I_F = f(V_F)$






### IGBT, Switching losses vs. $I_C$


$V_{GE} = -8V / + 15V$ ,  $R_{G,on} = 2.5 \Omega$

$R_{G,off} = 5.0 \Omega$ ,  $V_{CE} = 400V$ ,  $E_{on}$  &  $E_{off} = f(I_C)$



### IGBT, Capacitance characteristics


$V_{GE} = 0V$ ,  $T_j = 25^\circ C$ ,  $f = 100 \text{ kHz}$ ,  $C = f(V_{CE})$



### IGBT, Switching losses vs. $R_G$


$V_{GE} = -8V / + 15V$ ,  $V_{CE} = 400V$ ,  $I_C = 450A$

$E_{on}$  &  $E_{off} = f(R_G)$




### NTC-Thermistor-temperature characteristic

$R = f(T_{NTC})$







Diode, Switching losses vs.  $I_F$   
 $R_G = 2.5 \Omega$ ,  $V_R = 400V$ ,  $E_{rec} = f(I_F)$




Reverse bias safe operating area (RBSOA)  
 $V_{GE} = -8V / +15V$ ,  $R_{G,off} = 5.0 \Omega$ ,  $T_j = 175^\circ C$



Diode, Switching losses vs.  $R_G$   
 $I_F = 450A$ ,  $V_R = 400V$ ,  $E_{rec} = f(R_G)$



IGBT Total gate charge characteristic  
 $V_{CE} = 400V$ ,  $I_C = 450A$ ,  $T_j = 25^\circ C$   
 $V_{GE} = f(Q_G)$






ACTRON TECHNOLOGY CORP.

### IGBT Transient thermal impedance

$$Z_{thJF} = f(t_p)$$


$\Delta V/\Delta t = 10 \text{ dm}^3/\text{min}$ ,  $T_F = 70^\circ\text{C}$



### Diode Transient thermal impedance







$$Z_{thJF} = f(t_p)$$

$\Delta V/\Delta t = 10 \text{ dm}^3/\text{min}$ ,  $T_F = 70^\circ\text{C}$





## Package Outlines



## **IMPORTANT NOTICE AND DISCLAIMER**

**Edition 2024-11**

**Published by  
Actron Technology**

**The information given in this document shall declare not to regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and / or any information regarding the application of the device. Actron technology provides such information, and other resources “as Is”, and disclaims all warranties, express and implied, including without limitation any implied warranties of merchantability, fitness for a particular purpose or non-infringement of third party intellectual property rights.**

**These resources are intended for skilled developers designing with Actron products. You are solely responsible for (1) selecting the appropriate Actron products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.**

**For further information on technology, delivery terms and conditions and prices, please contact the Actron Technology. (<https://www.actron.com.tw/tw>)**

**Warnings Due to technical requirements, components may contain dangerous substances For information on the types in question, please contact the Actron Technology. Actron Technology components may be used in special applications only with the express written approval of Actron Technology.**



**Trademarks of Actron Technology  
Copyright © 2024 Actron Technology — All Rights Reserved.**

